

**STANDARD DEPARTURE CHART -
INSTRUMENT (SID) - ICAO**

**AD 2 - EKCH
RNAV SID RWY 22 R - 4
København / Kastrup**

Tabular description:

RNAV RWY 22 R via BETUD 2C

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	RUBAT	Y	217 / (221.2)	-4.0	-	-	-	-	-	RNAV 1
002	TF	BISTA	-	211 / (214.9)	-4.0	26.7	-	-	-	-	RNAV 1
003	TF	BETUD	-	126 / (130.4)	-4.0	18.1	L	-	-	-	RNAV 1

RNAV RWY 22 R via NEXEN 2C

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	RUBAT	Y	217 / (221.2)	-4.0	-	-	-	-	-	RNAV 1
002	TF	BISTA	-	211 / (214.9)	-4.0	26.7	-	-	-	-	RNAV 1
003	TF	NEXEN	-	212 / (216.3)	-4.0	29.2	-	-	-	-	RNAV 1

RNAV RWY 22 R via KOPEX 2C

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	RUBAT	Y	217 / (221.2)	-4.0	-	-	-	-	-	RNAV 1
002	TF	MAXEL	-	223 / (226.7)	-4.0	31.4	-	-	-	-	RNAV 1
003	TF	KOPEX	-	222 / (226.4)	-4.0	20.8	-	-	-	-	RNAV 1

RNAV RWY 22 R via LANGO 2C

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	RUBAT	Y	217 / (221.2)	-4.0	-	-	-	-	-	RNAV 1
002	TF	TOBIS	-	234 / (238.4)	-4.0	35.9	R	-	-	-	RNAV 1
003	TF	LANGO	-	233 / (237.2)	-4.0	33.7	-	-	-	-	RNAV 1

RNAV RWY 22 R via ODDON 1C

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	RUBAT	Y	217 / (221.2)	-4.0	-	-	-	-	-	RNAV 1
002	DF	CH815	-	-	-4.0	-	R	-	-	-	RNAV 1
003	TF	DOBEL	-	269 / (273.3)	-4.0	31.4	-	-	-	-	RNAV 1
004	TF	ODDON	-	263 / (266.9)	-4.0	25.1	-	-	-	-	RNAV 1

RNAV RWY 22 R via GOLGA 2C

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	RUBAT	Y	217 / (221.2)	-4.0	-	-	-	-	-	RNAV 1
002	DF	CH815	-	-	-4.0	-	R	-	-	-	RNAV 1
003	TF	CH816	-	350 / (354.0)	-4.0	12.0	R	-	-	-	RNAV 1
004	TF	MIRGO	-	325 / (329.1)	-4.0	18.1	L	-	-	-	RNAV 1
005	TF	GOLGA	-	327 / (330.5)	-4.0	20.6	-	-	-	-	RNAV 1

Changes : ODN VOR and ODN 2C withdrawn. WPT ODDON and ODDON 1C added. Editorial.