

Instrument Approach Procedure Coding Tables:

BGPT RNP A via BAMUG, GENSA and NANOK.

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	BAMUG	-	-	+23.0	-	-	+3800	-	-	RNP APCH
020	TF	PT351	-	076 / (052.6)	+23.0	5.0	L	+3200	-	-	RNP APCH
010	IF	GENSA	-	-	+23.0	-	-	+5100	-	-	RNP APCH
020	TF	PT351	-	346 / (322.8)	+23.0	5.0	-	+3200	-	-	RNP APCH
010	IF	NANOK	-	-	+23.0	-	-	+5300	-	-	RNP APCH
020	TF	PT351	-	256 / (232.9)	+23.0	5.0	R	+3200	-	-	RNP APCH
030	TF	PT353	-	346 / (322.7)	+23.0	4.4	-	+2600	-	-	RNP APCH
040	TF	RW35	Y	346 / 322.6)	+23.0	6.6	-	-	-	3.50°/50	RNP APCH
050	CA	-	-	346 / (322.6)	+23.0	-	-	@1500	-	-	RNP APCH
060	DF	BAMUG	-	-	+23.0	-	L	@3200	-	-	RNP APCH
070	HM	BAMUG	Y	076 / (052.6)	+23.0	-	R	@3200	-	-	RNP APCH

BGPT RNP A waypoint coordinates:

Waypoint Identifier	Coordinates
BAMUG (IAF)	61 48 58.54 N 049 34 14.25 W
GENSA (IAF)	61 48 01.62 N 049 19 28.34 W
NANOK (IAF)	61 55 00.70 N 049 17 25.97 W
PT351 (IF)	61 51 59.86 N 049 25 50.95 W
PT353 (FAF)	61 55 30.06 N 049 31 30.38 W
RW35 (MAPt)	62 00 42.81 N 049 39 58.66 W

Changes : PT352 withdrawn and PT353 added. Altitudes changed. VPA/TCH changed.