

Instrument Approach Procedure Coding Tables:

BGMQ RNP RWY 33 via ASGAL, OGIVI and DITUR

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	ASGAL	-	-	+26.0	-	-	+6800	-	-	RNP APCH
015	TF	MQ403	-	243 / (217.4)	+26.0	5.0	-	+4500	-	-	RNP APCH
020	TF	MQ402	-	243 / (217.3)	+26.0	5.0	R	+3100	-	-	RNP APCH
010	IF	OGIVI	-	-	+26.0	-	-	+5700	-	-	RNP APCH
020	TF	MQ402	-	333 / (307.4)	+26.0	7.0	-	+3100	-	-	RNP APCH
010	IF	DITUR	-	-	+26.0	-	-	+3800	-	-	RNP APCH
020	TF	MQ402	-	063 / (037.1)	+26.0	5.0	L	+3100	-	-	RNP APCH
030	TF	MQ401	-	333 / (307.2)	+26.0	4.3	-	+2200	-	-	RNP APCH
040	TF	MQ400	Y	333 / (307.1)	+26.0	4.5	-	-	-	3.7°/50	RNP APCH
050	DF	MQ404	-	-	+26.0	-	L	-	-130	-	RNP APCH
060	TF	MQ405	-	213 / (186.8)	+26.0	5.5	L	-	-	-	RNP APCH
070	TF	DITUR	-	131 / (105.0)	+26.0	8.7	L	@3100	-	-	RNP APCH
080	HM	DITUR	Y	063 / (037.1)	+26.0	-	R	@3100	-	-	RNP APCH

BGMQ RNP Waypoint coordinates:

Waypoint Identifier	Coordinates
ASGAL (IAF)	65 26 50.30N 052 23 21.34W
OGIVI (IAF)	65 14 40.79N 052 24 35.34W
DITUR (IAF/MAHF)	65 14 56.21N 052 45 02.28W
MQ400 (MAPt)	65 24 11.96N 052 54 36.84W
MQ401 (FAF)	65 21 28.26N 052 45 56.37W
MQ402 (IF)	65 18 54.58N 052 37 50.80W
MQ403	65 22 52.61N 052 30 37.16W
MQ404	65 22 38.03N 053 03 24.64W
MQ405	65 17 11.38N 053 04 57.99W

Changes: New procedure.