



Changes : Holding positions and intermediate holding positions changed. Maintenance area added.

Datum : WGS-84

NR	Direction	THR PSN	Pavement Strength	Day marking	Declared distances					APCH and RWY LGT (Unless otherwise stated lighting is LIH adjustable)					
					PSN TWY	TORA	TODA	ASDA	LDA	APCH	THR ID LGT	THR	PAPI	Edge	End
03	030.9° GEO 026.9° MAG	55 34 42.25N 012 07 25.85E	Asphalt PCN 30 F / C / X / T	THR RWY NR TDZ 21 only Centre line Side stripes	A1/A2	1501	1501	1501	1501	450 M White	Green	3°	1500 M White	Red	
A3	758	758			758										
21	210.9° GEO 206.9° MAG	55 35 23.85N 012 08 09.85E	Asphalt PCN 36 F / C / X / T	THR RWY NR TDZ 11 only Centre line Side stripes	A4/A5	1500	1500	1500	1500	820 M White	Green	3° MEHT 51 FT	1500 M White	Red	
B	1117	1117			1117										
11	116.3° GEO 112.3° MAG	55 35 23.93N 012 06 56.30E			Asphalt PCN 36 F / C / X / T	THR RWY NR TDZ 11 only Centre line Side stripes	B1/B2	1740	1740	1799	1740	789 M White	Green	3° MEHT 51 FT	1799 M White
B3	1178	1178	1237												
A	815	815	874	1740			420 M White	Green	Green	3°	59 M Red 1740 M White	Red			
B4/B5	1799	1799	1799												
29	296.3° GEO 292.3° MAG	55 34 59.03N 012 08 25.39E	Asphalt PCN 36 F / C / X / T	THR RWY NR TDZ 11 only Centre line Side stripes	A	940	940	940	1740	420 M White	Green	Green	3°	59 M Red 1740 M White	Red
B4/B5	1500	1500			1500										

TAXIWAYS	
Width :	M : 9 Other : 15
Pavement :	Asphalt
Strength :	B, B3, E and turn pads at RWY 11 and 29 : PCN 36 / F / C / X / U C : PCN 14 / F / C / Y / U Other TWY : PCN 17 / F / C / Y / U
Day marking :	Centre line, Holding position Intermediate holding position Side stripes at turn pads RWY 11 and 29
Lighting :	Blue edge LIL, RGL. Turn pad RWY 11 and 29 : Blue edge LIL

OTHER : Secondary power supply : Yes, Switch-over time 15 SEC.
When RVR 800 M or below, switch-over time 1 SEC

OBSTACLES : All obstacles are marked by day and night