

Tabular description

RNAV RWY 30 via TESPI

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
001	IF	TESPI	-	-	-4.0	-	-	-	-	-	RNAV 1
002	TF	ROSBI	-	098 / (102.1)	-4.0	13.9	-	-	-	-	RNAV 1
003	TF	TNO	-	101 / (104.6)	-4.0	17.8	-	-	-250	-	RNAV 1
004	TF	CH969	-	088 / (091.9)	-4.0	10.8	-	- FL130	-	-	RNAV 1
005	TF	CH949	-	074 / (077.7)	-4.0	20.6	-	-	-	-	RNAV 1
006	TF	CH941	-	119 / (122.9)	-4.0	7.7	R	-	-	-	RNAV 1
007	TF	CH932	-	119 / (123.0)	-4.0	8.7	-	-	-	-	RNAV 1
008	TF	CH925	-	119 / (123.2)	-4.0	6.6	-	-	-	-	RNAV 1
009	TF	HOFFO	-	120 / (124.2)	-4.0	6.4	-	-4000	@220	-	RNAV 1
010	FM	HOFFO	-	119 / (123.2)	-4.0	-	-	-	-	-	RNAV 1

RNAV RWY 30 via TUDLO

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
001	IF	TUDLO	-	-	-4.0	-	-	-	-	-	RNAV 1
002	TF	LUGAS	-	069 / (073.2)	-4.0	11.3	-	-	-	-	RNAV 1
003	TF	KOR	-	070 / (073.7)	-4.0	23.8	-	-FL120	-250	-	RNAV 1
004	TF	CH947	-	106 / (110.3)	-4.0	16.8	R	-	-	-	RNAV 1
005	TF	CH930	-	080 / (084.4)	-4.0	17.1	L	-	-	-	RNAV 1
006	TF	COPHO	-	071 / (074.7)	-4.0	11.0	-	-4000	@220	-	RNAV 1
007	FM	COPHO	-	119 / (123.2)	-4.0	-	R	-	-	-	RNAV 1

RNAV RWY 30 via MONAK

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
001	IF	MONAK	-	-	-4.0	-	-	-	-	-	RNAV 1
002	TF	OLPIB	-	030 / (034.0)	-4.0	4.1	-	-	-	-	RNAV 1
003	TF	KUBIS	-	011 / (014.8)	-4.0	13.8	L	-FL090	-250	-	RNAV 1
004	TF	CH930	-	019 / (023.2)	-4.0	9.5	-	-	-	-	RNAV 1
005	TF	COPHO	-	071 / (074.7)	-4.0	11.0	R	-4000	@220	-	RNAV 1
006	FM	COPHO	-	119 / (123.2)	-4.0	-	R	-	-	-	RNAV 1

RNAV RWY 30 via TIDVU

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	IF	TIDVU	-	-	-4.0	-	-	-	-	-	RNAV 1
002	TF	WUPJA	-	319 / (322.6)	-4.0	16.3	-	-FL080	-250	-	RNAV 1
003	TF	CH940	-	300 / (303.6)	-4.0	16.6	L	-	-	-	RNAV 1
004	TF	CH932	-	209 / (213.3)	-4.0	6.3	L	-	-	-	RNAV 1
005	TF	CH925	-	119 / (123.2)	-4.0	6.6	-	-	-	-	RNAV 1
006	TF	HOFFO	-	120 / (124.2)	-4.0	6.4	-	-4000	@220	-	RNAV 1
007	FM	HOFFO	-	119 / (123.2)	-4.0	-	-	-	-	-	RNAV 1

RNAV RWY 30 via ERNOV

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	IF	ERNOV	-	-	-4.0	-	-	-FL110	-250	-	RNAV 1
002	TF	CH956	-	197 / (200.9)	-4.0	14.2	-	-	-	-	RNAV 1
003	TF	CH949	-	197 / (200.8)	-4.0	7.0	-	-	-	-	RNAV 1
004	TF	CH941	-	119 / (122.9)	-4.0	7.7	L	-	-	-	RNAV 1
005	TF	CH932	-	119 / (123.0)	-4.0	8.7	-	-	-	-	RNAV 1
006	TF	CH925	-	119 / (123.2)	-4.0	6.6	-	-	-	-	RNAV 1
007	TF	HOFFO	-	120 / (124.2)	-4.0	6.4	-	-4000	@220	-	RNAV 1
008	FM	HOFFO	-	119 / (123.2)	-4.0	-	-	-	-	-	RNAV 1

Changes: WPTs CDA and HUFOH withdrawn. WPTs CH925, HOFFO and OLPIB added. Editorial.