

Recommended Coding Tables:

BGGH RNP A.

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	NIPOT	-	-	+24.0	-	-	+5400	-	-	RNP APCH
020	TF	GONEN	-	094 / (069.8)	+24.0	5.0	L	+3300	-	-	RNP APCH
010	IF	UVIRI	-	-	+24.0	-	-	+4600	-	-	RNP APCH
020	TF	GONEN	-	024 / (000.0)	+24.0	5.0	-	+3300	-	-	RNP APCH
010	IF	ADKUT	-	-	+24.0	-	-	+5900	-	-	RNP APCH
020	TF	GONEN	-	314 / (290.2)	+24.0	5.5	R	+3500	-	-	RNP APCH
010	IF	GONEN	-	-	+24.0	-	-	+3300	-	-	RNP APCH
020	TF	GHF40	-	027 / (003.0)	+24.0	5.4	-	+2500	-	-	RNP APCH
030	TF	GHM40	Y	027 / (003.1)	+24.0	6.4	-	-	-	3.20° / -	RNP APCH
040	TF	GH400	Y	027 / (003.1)	+24.0	4.0	L	-	-	-	RNP APCH
050	DF	CALRI	-	-	+24.0	-	-	+3000	-170	-	RNP APCH
060	HM	CALRI	Y	131 / (107.2)	+24.0	-	R	+3000	-170	-	RNP APCH

BGGH RNP A waypoint coordinates:

Waypoint Identifier	Coordinates
NIPOT (IAF)	63 56 49.78N 051 54 58.77W
UVIRI (IAF)	63 53 33.41N 051 44 19.78W
ADKUT (IAF)	63 56 39.43N 051 32 37.36W
GONEN (IF)	63 58 32.45N 051 44 19.78W
GHF40 (FAF)	64 03 52.13N 051 43 40.97W
GHM40 (MAPt)	64 10 14.12N 051 42 54.28W
GH400 (MATF)	64 14 13.00N 051 42 24.90W
CALRI (MAHF)	64 15 02.89N 052 06 53.01W

Changes : Completely revised procedure. Waypoints ELTUX and ADMIP withdrawn. WPTS GHF40, GHM40, GH400 and CALRI added.