

**STANDARD ARRIVAL CHART -
INSTRUMENT (STAR) - ICAO**

**AD 2 - EKCH
RNAV STAR RWY 22 L / R - 3
København / Kastrup**

**Tabular description
RNAV RWY 22 L / R via TESPI**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	TESPI	-	-	-4.0	-	-	-	-	-	RNAV 1
020	TF	ROSBI	-	098 / (102.1)	-4.0	13.9	-	-	-	-	RNAV 1
030	TF	TNO	-	101 / (104.6)	-4.0	17.8	L	-	-250	-	RNAV 1
040	TF	CH653	-	092 / (095.6)	-4.0	14.2	-	-FL130	-	-	RNAV 1
050	TF	CH645	-	092 / (095.9)	-4.0	8.3	-	-	-	-	RNAV 1
060	TF	CH638	-	092 / (096.1)	-4.0	6.9	-	-	-	-	RNAV 1
070	TF	CH631	-	092 / (096.3)	-4.0	7.2	L	-	-	-	RNAV 1
080	TF	CH626	-	059 / (063.1)	-4.0	5.0	L	-5000	-	-	RNAV 1
090	TF	ABEGI	-	037 / (041.3)	-4.0	7.5	-	-4000	@220	-	RNAV 1
100	FM	ABEGI	-	037 / (041.3)	-4.0	-	-	-	-	-	RNAV 1

RNAV RWY 22 L / R via TUDLO

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	TUDLO	-	-	-4.0	-	-	-	-	-	RNAV 1
020	TF	LUGAS	-	069 / (073.2)	-4.0	11.3	-	-	-	-	RNAV 1
030	TF	KOR	-	070 / (073.7)	-4.0	23.8	L	-	-250	-	RNAV 1
040	TF	CH654	-	038 / (041.5)	-4.0	15.3	-	-FL120	-	-	RNAV 1
050	TF	CH645	-	038 / (041.8)	-4.0	8.6	R	-	-	-	RNAV 1
060	TF	CH638	-	092 / (096.1)	-4.0	6.9	-	-	-	-	RNAV 1
070	TF	CH631	-	092 / (096.3)	-4.0	7.2	L	-	-	-	RNAV 1
080	TF	CH626	-	059 / (063.1)	-4.0	5.0	L	-5000	-	-	RNAV 1
090	TF	ABEGI	-	037 / (041.3)	-4.0	7.5	-	-4000	@220	-	RNAV 1
100	FM	ABEGI	-	037 / (041.3)	-4.0	-	-	-	-	-	RNAV 1

RNAV RWY 22 L / R via MONAK

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	MONAK	-	-	-4.0	-	-	-	-	-	RNAV 1
020	TF	OLPIB	-	030 / (034.0)	-4.0	4.1	-	-	-	-	RNAV 1
030	TF	NEKSO	-	030 / (033.8)	-4.0	16.7	L	-	-250	-	RNAV 1
040	TF	CH643	-	014 / (018.0)	-4.0	8.3	-	-FL090	-	-	RNAV 1
050	TF	CH636	-	014 / (018.0)	-4.0	6.9	-	-	-	-	RNAV 1
060	TF	CH630	-	014 / (018.1)	-4.0	5.3	-	-	-	-	RNAV 1
070	TF	CH625	-	018 / (022.1)	-4.0	4.6	R	-5000	-	-	RNAV 1
080	TF	ADOVI	-	037 / (041.4)	-4.0	7.5	-	-4000	@220	-	RNAV 1
090	FM	ADOVI	-	037 / (041.4)	-4.0	-	-	-	-	-	RNAV 1

RNAV RWY 22 L / R via TIDVU

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	TIDVU	-	-	-4.0	-	-	-	-	-	RNAV 1
020	TF	ESJAH	-	283 / (287.0)	-4.0	10.1	L	-FL080	-250	-	RNAV 1
030	TF	CH641	-	260 / (264.0)	-4.0	11.8	R	-	-	-	RNAV 1
040	TF	CH636	-	289 / (292.5)	-4.0	5.4	-	-	-	-	RNAV 1
050	TF	CH630	-	014 / (018.1)	-4.0	5.3	-	-	-	-	RNAV 1
060	TF	CH625	-	018 / (022.1)	-4.0	4.6	R	-5000	-	-	RNAV 1
070	TF	ADOVI	-	037 / (041.4)	-4.0	7.5	-	-4000	@220	-	RNAV 1
080	FM	ADOVI	-	037 / (041.4)	-4.0	-	-	-	-	-	RNAV 1

RNAV RWY 22 L / R via ERNOV

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	ERNOV	-	-	-4.0	-	-	-FL110	-250	-	RNAV 1
020	TF	CH647	-	191 / (194.7)	-4.0	14.3	-	-	-	-	RNAV 1
030	TF	CH637	-	191 / (194.9)	-4.0	10.9	L	-	-	-	RNAV 1
040	TF	CH631	-	122 / (125.7)	-4.0	5.3	L	-	-	-	RNAV 1
050	TF	CH626	-	059 / (063.1)	-4.0	5.0	L	-5000	-	-	RNAV 1
060	TF	ABEGI	-	037 / (041.3)	-4.0	7.5	-	-4000	@220	-	RNAV 1
070	FM	ABEGI	-	037 / (041.3)	-4.0	-	-	-	-	-	RNAV 1

Changes: Altitude restriction for WPT CH625 and CH626 added.