

**STANDARD ARRIVAL CHART -
INSTRUMENT (STAR) - ICAO**

**AD 2 - EKCH
RNAV STAR RWY 04 L / R - 3
København / Kastrup**

Tabular description

RNAV RWY 04 L / R via TESPI

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
001	IF	TESPI	-	-	-4.0	-	-	-	-	-	RNAV 1
002	TF	ROSBI	-	098 / (102.1)	-4.0	13.9	-	-	-	-	RNAV 1
003	TF	TNO	-	101 / (104.6)	-4.0	17.8	-	-	-250	-	RNAV 1
004	TF	CH750	-	094 / (097.9)	-4.0	11.3	-	-FL130	-	-	RNAV 1
005	TF	CH742	-	094 / (098.2)	-4.0	8.0	-	-	-	-	RNAV 1
006	TF	CH734	-	094 / (098.3)	-4.0	8.0	-	-	-	-	RNAV 1
007	TF	CH727	-	135 / (139.4)	-4.0	8.6	R	-5000	-	-	RNAV 1
008	TF	ERPUK	-	217 / (221.1)	-4.0	8.4	R	-4000	@220	-	RNAV 1
009	FM	ERPUK	-	217 / (221.1)	-4.0	-	-	-	-	-	RNAV 1

RNAV RWY 04 L / R via TUDLO

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
001	IF	TUDLO	-	-	-4.0	-	-	-	-	-	RNAV 1
002	TF	LUGAS	-	069 / (073.2)	-4.0	11.3	-	-	-	-	RNAV 1
003	TF	KOR	-	070 / (073.7)	-4.0	23.8	-	-FL120	-250	-	RNAV 1
004	TF	CH751	-	052 / (055.6)	-4.0	9.8	L	-	-	-	RNAV 1
005	TF	CH740	-	052 / (056.0)	-4.0	9.7	-	-	-	-	RNAV 1
006	TF	CH734	-	037 / (040.6)	-4.0	7.0	L	-	-	-	RNAV 1
007	TF	CH727	-	135 / (139.4)	-4.0	8.6	R	-5000	-	-	RNAV 1
008	TF	ERPUK	-	217 / (221.1)	-4.0	8.4	R	-4000	@220	-	RNAV 1
009	FM	ERPUK	-	217 / (221.1)	-4.0	-	-	-	-	-	RNAV 1

RNAV RWY 04 L / R via MONAK

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
001	IF	MONAK	-	-	-4.0	-	-	-	-	-	RNAV 1
002	TF	OLPIB	-	030 / (034.0)	-4.0	4.1	-	-	-	-	RNAV 1
003	TF	NEKSO	-	030 / (033.8)	-4.0	16.7	-	-FL090	-250	-	RNAV 1
004	TF	CH731	-	025 / (028.8)	-4.0	8.4	-	-	-	-	RNAV 1
005	TF	CH724	-	305 / (308.5)	-4.0	8.2	L	-5000	-	-	RNAV 1
006	TF	DOPEM	-	217 / (221.2)	-4.0	5.0	L	-4000	@220	-	RNAV 1
007	FM	DOPEM	-	217 / (221.2)	-4.0	-	-	-	-	-	RNAV 1

RNAV RWY 04 L / R via TIDVU

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
001	IF	TIDVU	-	-	-4.0	-	-	-	-	-	RNAV 1
002	TF	ESJAH	-	283 / (287.0)	-4.0	10.1	-	-FL080	-250	-	RNAV 1
003	TF	CH743	-	241 / (245.2)	-4.0	9.8	L	-	-	-	RNAV 1
004	TF	CH737	-	211 / (215.0)	-4.0	6.9	L	- FL060	-	-	RNAV 1
005	TF	CH731	-	303 / (306.8)	-4.0	5.6	R	-	-	-	RNAV 1
006	TF	CH724	-	305 / (308.5)	-4.0	8.2	-	-5000	-	-	RNAV 1
007	TF	DOPEM	-	217 / (221.2)	-4.0	5.0	L	-4000	@220	-	RNAV 1
008	FM	DOPEM	-	217 / (221.2)	-4.0	-	-	-	-	-	RNAV 1

RNAV RWY 04 L / R via ERNOV

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
001	IF	ERNOV	-	-	-4.0	-	-	-FL110	-250	-	RNAV 1
002	TF	CH744	-	176 / (179.7)	-4.0	17.9	-	-	-	-	RNAV 1
003	TF	CH727	-	196 / (200.1)	-4.0	17.3	R	-5000	-	-	RNAV 1
004	TF	ERPUK	-	217 / (221.1)	-4.0	8.4	R	-4000	@220	-	RNAV 1
005	FM	ERPUK	-	217 / (221.1)	-4.0	-	-	-	-	-	RNAV 1

Changes: Altitude restriction for WPT CH724 and CH727 added.