

Instrument Approach Procedure Coding Tables:

EKCH RNP RWY 30.

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	ELDAB	-	-	-4.0	-	-	+3000	-220	-	RNP APCH
020	TF	ORZIH	-	209 / (213.2)	-4.0	4.0	R	+3000	-220	-	RNP APCH
010	IF	HAXHI	-	-	-4.0	-	-	+3000	-220	-	RNP APCH
020	TF	ORZIH	-	029 / (033.1)	-4.0	4.0	L	+3000	-220	-	RNP APCH
010	IF	ORZIH	-	-	-4.0	-	-	+3000	-220	-	RNP APCH
020	TF	CH30F	-	299 / (303.3)	-4.0	4.2	-	+3000	-	-	RNP APCH
030	CF	RW30	Y	299 / (303.3)	-4.0	9.0	-	-	-	3.0° / 49	RNP APCH
040	DF	CH301	-	299 / (303.3)	-4.0	16.5	-	+3000	-	-	RNP APCH
050	FM	CH301	-	299 / (303.3)	-4.0	-	-	+3000	-	-	RNP APCH

EKCH RNP RWY 30 waypoint coordinates:

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
ELDAB (IAF)	55 32 57.73N 013 03 17.80E	CH30F (FAP/FAF)	55 31 54.22N 012 53 18.46E
HAXHI (IAF)	55 26 16.42N 012 55 36.87E	RW30 (MAPt)	55 36 49.87N 012 40 01.01E
ORZIH (IAF/IF)	55 29 37.14N 012 59 27.01E	CH301	55 45 49.78N 012 15 36.09E

Changes: Coding Table revised. WPT ELDAB and HAXHI added. WPT COPHO and HOFFO withdrawn. FAS Datablock moved to RNP RWY 30 - 3.