

Instrument Approach Procedure Coding Tables:

BGAA RNP RWY 11 via VIGZE, ASSIW and CAGMO

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	VIGZE	-	-	+29.0	-	-	A2000+	-	-	RNP APCH
020	TF	ASSIW	-	177 / (147.8)	+29.0	5.0	L	A2000+	-	-	RNP APCH
010	IF	ASSIW	-	-	+29.0	-	-	A2000+	-	-	RNP APCH
010	IF	CAGMO	-	-	+29.0	-	-	A2500+	-	-	RNP APCH
020	TF	ASSIW	-	037 / (007.8)	+29.0	5.0	R	A2000+	-	-	RNP APCH
030	TF	AAF11	-	107 / (077.9)	+29.0	4.0	-	A1800+	-	-	RNP APCH
040	TF	RW11	Y	107 / (078.0)	+29.0	4.9	-	-	-	3.20°/50	RNP APCH
050	CA	-	-	107 / (078.0)	+29.0	-	-	A1000+	-	-	RNP APCH
060	DF	ASSIW	-	-	+29.0	-	L	-	-	-	RNP APCH
070	HM	ASSIW	Y	107 / (077.9)	+29.0	-	L	A2000	-	-	RNP APCH

BGAA RNP RWY 11 waypoint coordinates:

Waypoint Identifier	Coordinates
VIGZE (IAF)	68 45 38.46N 053 18 56.95W
ASSIW (IAF / IF / MAHF)	68 41 25.45N 053 11 38.50W
CAGMO (IAF)	68 36 29.31N 053 13 30.69W
AAF11 (FAP/ FAF)	68 42 15.31N 053 00 55.78W
RW11 (MAPt)	68 43 16.03N 052 47 39.85W

Changes: New procedure.