

Tabular description:

RNAV RWY 30 via KEMAX 6D

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	BAFIQ	Y	299 / (303.2)	-4.0	-	-	-	-	-	RNAV 1
002	DF	CH822	-	-	-4.0	-	-	-	-	-	RNAV 1
003	TF	CH829	-	031 / (034.8)	-4.0	15.1	R	-	-	-	RNAV 1
004	TF	KEMAX	-	060 / (063.8)	-4.0	29.4	R	-	-	-	RNAV 1

RNAV RWY 30 via SIMEG 9D

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	BAFIQ	Y	299 / (303.2)	-4.0	-	-	-	-	-	RNAV 1
002	DF	CH825	-	-	-4.0	-	-	-	-	-	RNAV 1
003	TF	CH827	-	192 / (195.8)	-4.0	9.3	L	-	-	-	RNAV 1
004	TF	CH828	-	086 / (089.8)	-4.0	14.6	L	-	-	-	RNAV 1
005	TF	CH830	-	119 / (122.9)	-4.0	7.4	R	-	-	-	RNAV 1
006	TF	SIMEG	-	119 / (123.0)	-4.0	23.9	-	-	-	-	RNAV 1

RNAV RWY 30 via SALLO 1D

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	BAFIQ	Y	299 / (303.2)	-4.0	-	-	-	-	-	RNAV 1
002	DF	CH825	-	-	-4.0	-	-	-	-	-	RNAV 1
003	TF	CH827	-	192 / (195.8)	-4.0	9.3	L	-	-	-	RNAV 1
004	TF	CH828	-	086 / (089.8)	-4.0	14.6	L	-	-	-	RNAV 1
005	TF	CH830	-	119 / (122.9)	-4.0	7.4	R	-	-	-	RNAV 1
006	TF	SALLO	-	150 / (153.8)	-4.0	36.9	R	-	-	-	RNAV 1

RNAV RWY 30 via BETUD 3D

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	BAFIQ	Y	299 / (303.2)	-4.0	-	-	-	-	-	RNAV 1
002	DF	CH825	-	-	-4.0	-	-	-	-	-	RNAV 1
003	TF	CH826	-	219 / (223.2)	-4.0	8.4	L	-	-	-	RNAV 1
004	TF	BISTA	-	184 / (187.7)	-4.0	23.0	L	-	-	-	RNAV 1
005	TF	BETUD	-	126 / (130.4)	-4.0	18.1	L	-	-	-	RNAV 1

RNAV RWY 30 via NEXEN 3D

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	BAFIQ	Y	299 / (303.2)	-4.0	-	-	-	-	-	RNAV 1
002	DF	CH825	-	-	-4.0	-	-	-	-	-	RNAV 1
003	TF	CH826	-	219 / (223.2)	-4.0	8.4	L	-	-	-	RNAV 1
004	TF	BISTA	-	184 / (187.7)	-4.0	23.0	L	-	-	-	RNAV 1
005	TF	NEXEN	-	212 / (216.3)	-4.0	29.2	R	-	-	-	RNAV 1

Changes: Editorial.