

Instrument Approach Procedure Coding Tables:

BGSF RNP A via RUMAQ, FICWE and RIVOP

| Serial Number | Path Descriptor | Waypoint Identifier | Fly-over | Course/Track °M(°T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (ft) | Speed (kt) | VPA/TCH | Navigation Specification |
|---------------|-----------------|---------------------|----------|---------------------|--------------------|---------------|----------------|---------------|------------|---------|--------------------------|
| 010 | IF | RUMAQ | - | - | +27.0 | - | - | A4000+ | - | - | RNP APCH |
| 020 | TF | SFI27 | - | 184 / (157.0) | +27.0 | 6.0 | R | A3800+ | - | - | RNP APCH |
| 010 | IF | FICWE | - | - | +27.0 | - | - | A5000+ | - | - | RNP APCH |
| 020 | TF | SFI27 | - | 274 / (247.3) | +27.0 | 6.0 | - | A3800+ | - | - | RNP APCH |
| 010 | IF | RIVOP | - | - | +27.0 | - | - | A4700+ | - | - | RNP APCH |
| 020 | TF | SFI27 | - | 004 / (337.2) | +27.0 | 6.0 | L | A3800+ | - | - | RNP APCH |
| 030 | TF | SFF27 | - | 274 / (247.1) | +27.0 | 5.5 | - | A2800+ | - | - | RNP APCH |
| 040 | TF | SFM27 | Y | 274 / (246.9) | +27.0 | 6.4 | - | - | - | -3.3°/- | RNP APCH |
| 050 | CA | - | - | 274 / (246.7) | +27.0 | - | - | A3000+ | - | - | RNP APCH |
| 060 | DF | KEFOP | - | - | +27.0 | - | - | - | - | - | RNP APCH |
| 070 | HM | KEFOP | Y | 088 / (061.1) | +27.0 | - | R | A4000 | - | - | RNP APCH |

BGSF RNP A waypoint coordinates:

| Waypoint Identifier | Coordinates |
|---------------------|----------------------------|
| RUMAQ (IAF) | 67 11 32.28N 050 16 54.86W |
| FICWE (IAF) | 67 08 20.88N 049 56 45.12W |
| RIVOP (IAF) | 67 00 31.21N 050 04 57.68W |
| KEFOP (MAHF) | 66 53 50.33N 051 14 55.26W |
| SFI27 (IF) | 67 06 01.86N 050 10 54.92W |
| SFF27 (FAF) | 67 03 53.80N 050 23 48.61W |
| SFM27 (MAPt) | 67 01 23.37N 050 38 46.74W |

Changes: New procedure.