

Recommended Coding Tables:

BGGH RNP Y RWY 22

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	VETOX	-	-	+24.0	-	-	+5400	-	-	RNP APCH
020	TF	GH22I	-	132 / (107.7)	+24.0	5.0	R	+4400	-	-	RNP APCH
010	IF	GETDA	-	-	+24.0	-	-	+7400	-	-	RNP APCH
020	TF	GH22I	-	222 / (197.9)	+24.0	8.0	-	+4400	-	-	RNP APCH
010	IF	ERALA	-	-	+24.0	-	-	+7400	-	-	RNP APCH
020	TF	GH22I	-	312 / (288.1)	+24.0	7.5	L	+4400	-	-	RNP APCH
010	IF	GH22I	-	-	+24.0	-	-	+4400	-	-	RNP APCH
020	TF	GH600	-	222 / (197.8)	+24.0	4.9	-	+3200	-	-	RNP APCH
030	TF	GH601	Y	222 / (197.8)	+24.0	7.2	R	-	-185	3.20°/50	RNP APCH
040	DF	GH602	Y	-	+24.0	-	L	-	-220	-	RNP APCH
050	DF	GH603	-	-	+24.0	-	L	-	-220	-	RNP APCH
060	TF	ERALA	-	042 / (017.8)	+24.0	21.1	-	+7400	-	-	RNP APCH
070	HM	ERALA	Y	312 / (288.1)	+24.0	-	R	+7400	-230	-	RNP APCH

BGGH RNP Y RWY 22 waypoint coordinates:

Waypoint Identifier	Coordinates
VETOX (IAF)	64 26 18.64N 051 41 54.78W
GETDA (IAF)	64 32 23.04N 051 25 15.27W
ERALA (IAF / MAHF)	64 22 29.24N 051 14 29.10W
GH22I (IF)	64 24 47.50N 051 30 55.59W
GH600 (FAP/FAF)	64 20 05.65N 051 34 24.51W
GH601 (MAPt)	64 13 14.97N 051 39 26.71W
GH602 (MATF)	64 07 25.35N 051 52 15.54W
GH603 (MATF)	64 02 28.35N 051 29 22.48W
RW22	64 12 00.89N 051 40 20.94W

Changes : Speed limit withdrawn at serial 060. Editorial.