

**Instrument Approach Procedure Coding Tables:**

**EKCH RNP RWY 12.**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	LICXI	-	-	-4.0	-	-	+3000	-220	-	RNP APCH
020	TF	CH513	-	029 / (033.1)	-4.0	4.0	R	+3000	-	-	RNP APCH
010	IF	VECJA	-	-	-4.0	-	-	+3000	-220	-	RNP APCH
020	TF	CH513	-	119 / (123.0)	-4.0	2.0	-	+3000	-	-	RNP APCH
010	IF	TEBAQ	-	-	-4.0	-	-	+3000	-220	-	RNP APCH
020	TF	CH513	-	209 / (213.2)	-4.0	4.0	L	+3000	-	-	RNP APCH
030	TF	CH12F	-	119 / (123.1)	-4.0	4.0	-	+3000	-	-	RNP APCH
040	CF	RW12	Y	119 / (123.1)	-4.0	9.1	-	-	-	3.0° / 49	RNP APCH
050	DF	CH121	-	119 / (123.1)	-4.0	16.5	-	+3000	-	-	RNP APCH
060	FM	CH121	-	119 / (123.1)	-4.0	-	-	+3000	-	-	RNP APCH

**EKCH RNP RWY 12 waypoint coordinates:**

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
LICXI (IAF)	55 41 14.60N 012 15 06.62E	CH12F (FAP/FAF)	55 42 24.31N 012 24 54.03E
TEBAQ (IAF)	55 47 55.65N 012 22 51.14E	RW12 (MAPt)	55 37 26.94N 012 38 20.82E
VECJA (IAF)	55 45 39.83N 012 16 02.46E	CH121	55 28 26.14N 013 02 39.53E
CH513 (IF)	55 44 35.19N 012 18 58.56E		

Changes: Coding Table revised. WPT LICXI, TEBAQ and CH513 added. WPT FEDJO and AGTIC withdrawn. FAS Data block moved to RNP RWY 12-3.