

Instrument Approach Procedure Coding Tables:

BGSF RNP B via RUMAQ, FICWE and RIVOP

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	RUMAQ	-	-	+27.0	-	-	A4000+	-	-	RNP APCH
020	TF	SFI27	-	184 / (157.0)	+27.0	6.0	R	A3800+	-	-	RNP APCH
010	IF	FICWE	-	-	+27.0	-	-	A5000+	-	-	RNP APCH
020	TF	SFI27	-	274 / (247.3)	+27.0	6.0	-	A3800+	-	-	RNP APCH
010	IF	RIVOP	-	-	+27.0	-	-	A4700+	-	-	RNP APCH
020	TF	SFI27	-	004 / (337.2)	+27.0	6.0	L	A3800+	-	-	RNP APCH
030	TF	SFF27	-	274 / (247.1)	+27.0	5.5	-	A2800+	-	-	RNP APCH
040	TF	SFM27	Y	274 / (246.9)	+27.0	6.4	-	-	-	-3.3°/-	RNP APCH
050	DF	KEFOP	-	-	+27.0	-	-	-	-	-	RNP APCH
060	HM	KEFOP	Y	088 / (061.1)	+27.0	-	R	A4000	-	-	RNP APCH

BGSF RNP B waypoint coordinates:

Waypoint Identifier	Coordinates
RUMAQ (IAF)	67 11 32.28N 050 16 54.86W
FICWE (IAF)	67 08 20.88N 049 56 45.12W
RIVOP (IAF)	67 00 31.21N 050 04 57.68W
KEFOP (MAHF)	66 53 50.33N 051 14 55.26W
SFI27 (IF)	67 06 01.86N 050 10 54.92W
SFF27 (FAF)	67 03 53.80N 050 23 48.61W
SFM27 (MAPt)	67 01 23.37N 050 38 46.74W

Changes: New missed approach procedure.