

Instrument Approach Procedure Coding Tables:

EKOD ILS or LOC RWY 24 initial approach via ESIRU, RAVSI and TUNRU

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	ESIRU	-	-	-4.0	-	-	+2000	-	-210	RNAV 1
020	TF	OD242	-	166 / (170.0)	-4.0	5.0	R	+2000	-	-210	RNAV 1
010	IF	RAVSI	-	-	-4.0	-	-	+2000	-	-210	RNAV 1
020	TF	OD242	-	236 / (240.1)	-4.0	5.0	-	+2000	-	-210	RNAV 1
010	IF	TUNRU	-	-	-4.0	-	-	+2000	-	-210	RNAV 1
020	TF	OD242	-	306 / (310.1)	-4.0	5.0	L	+2000	-	-210	RNAV 1
010	IF	OD242	-	-	-4.0	-	-	+2000	-	-210	RNAV 1
020	TF	OD24F	-	236 / (240.0)	-4.0	4.1	-	+2000	-	-210	RNAV 1

EKOD ILS or LOC RWY 24 missed approach procedure:

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	CA	-	-	236 / (239.8)	-4.0	-	R	+2000	-210	-	RNAV 1
020	DF	OD24F	-	-	-4.0	-	-	@3000	-210	-	RNAV 1
030	HM	OD24F	-	236 (240.0)	-4.0	-	L	@3000	-210	-	RNAV 1

EKOD ILS or LOC RWY 24 waypoint coordinates:

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
ESIRU (IAF)	55 38 42.17N 010 34 04.84E	OD242 (IF)	55 33 47.32N 010 35 36.95E
RAVSI (IAF)	55 36 16.88N 010 43 14.91E	OD24F (FAP / FAF)	55 31 43.84N 010 29 20.68E
TUNRU (IAF)	55 30 34.74N 010 42 21.25E	MAPt	55 28 57.27N 010 20 55.66E

Changes: New procedure.