

Instrument Approach Procedure Coding Tables:

BGUQ RNP B via GOGAS, ELBOV and LAROL.

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	GOGAS	-	-	+30.0	-	-	A8100+	-	-	RNP APCH
020	TF	UQI51	-	199 / (169.1)	+30.0	15.0	L	A3000	-	-	RNP APCH
010	IF	ELBOV	-	-	+30.0	-	-	A7700+	-	-	RNP APCH
015	TF	LAROL	-	329 / (298.8)	+30.0	15.7	L	A3000+	-	-	RNP APCH
020	TF	UQI51	-	272 / (242.0)	+30.0	5.0	L	A3000	-	-	RNP APCH
010	IF	LAROL	-	-	+30.0	-	-	A3000	-	-	RNP APCH
020	TF	UQI51	-	272 / (242.0)	+30.0	5.0	L	A3000	-	-	RNP APCH
030	TF	UQF51	-	182 / (151.8)	+30.0	5.0	L	A2600	-	-	RNP APCH
040	TF	UQM51	Y	152 / (121.9)	+30.0	5.3	L	-	-130	3.50' / -	RNP APCH
050	DF	LAROL	-	-	-	-	-	A3000	-130	-	RNP APCH
060	HM	LAROL	Y	188 / (158.1)	+30.0	-	R	A3000	-170	-	RNP APCH

BGUQ RNP B waypoint coordinates:

Waypoint Identifier	Coordinates
GOGAS (IAF)	71 06 52.36N 053 13 11.25W
LAROL (IAF/MAHF)	70 54 33.43N 052 51 08.99W
ELBOV (IAF)	70 47 06.77N 052 09 19.71W
UQI51 (IF)	70 52 12.58N 053 04 33.62W
UQF51 (FAF)	70 47 49.08N 052 57 24.26W
UQM51 (MAPt)	70 45 02.32N 052 43 54.39W

Changes: VAR and MAG bearings changed. Chart designator