

1. Location Indicator/Name: BGFD - Narsaq Kujalleq

2. Geographical and Administrative Data

1. ARP PSN and site:	60 00 19N 044 39 28W
2. Distance and direction from city:	-
3. ELEV: REF temperature:	42 FT -
4. MAG VAR: Annual change:	22° W (JUN 2015) Decreasing 17'
5. ADM: Address:	Greenland Airports A/S KNI A/S Narsarmijit B477 DK-3922 Nanortalik Greenland TEL: +299 86 83 78 FAX: - E-mail: 013narsarmijit@kni.gl AFS: -
6. Types of traffic permitted:	VMC daylight
7. Remarks:	1. Maximum D-value limited to 20 M. 2. MTOM limited to 10 tonnes. 3. Maximum number of passenger seats limited to 19.

3. Operational Hours

1. AD:	MON-FRI 1100-1800 (1000-1700). SAT/SUN/HOL CLSD
2. Fuelling:	-

4. Aprons, Taxiways and Check Locations Data

1. Helicopter stand surface and strength:	Gravel -
---	-------------

5. Markings

1. Final approach and take-off markings:	Red/white truncated cones
2. TWY, air TWY, air transit route markers:	-
3. Remarks:	-

6. Heliport Obstacles

1. In APCH and TKOF areas

RWY Area affected	Type ELEV Markings/LGT	PSN
-		

Remarks: -

2. In circling area and at Heliport

Type ELEV Markings/LGT	PSN
-	

Remarks: -

1. Stedindikator/navn: BGFD - Narsaq Kujalleq

2. Geografiske og administrative data

1. ARP PSN og beliggenhed:	60 00 19N 044 39 28W
2. Afstand og retning fra by:	-
3. ELEV: REF temperatur:	42 FT -
4. MAG VAR: Årlig ændring:	22° W (JUN 2015) Aftagende 17'
5. ADM: Adresse:	Greenland Airports A/S KNI A/S Narsarmijit B477 DK-3922 Nanortalik Grønland TEL: +299 86 83 78 FAX: - E-mail: 013narsarmijit@kni.gl AFS: -
6. Tilladte trafiktyper:	VMC dag
7. Bemærkninger:	1. Maks D-værdi begrænses til 20 M. 2. MTOM begrænses til 10 tons. 3. Maks antal passagersæder begrænses til 19.

3. Tjenestetid

1. AD:	MON-FRI 1100-1800 (1000-1700). SAT/SUN/HOL CLSD
2. Tankning:	-

4. Forpladser, rulleveje og checkpunkt data

1. Helikopterstandplads overflade og styrke:	Grus -
--	-----------

5. Afmærkning

1. Landings- og start-afmærkning:	Rød/hvide keglestubbe
2. TWY, luft TWY, luft transit rute afmærkninger:	-
3. Bemærkninger:	-

6. Helikopterflyveplads hindringer

1. I APCH og TKOF områder

RWY Berørt område	Type ELEV Afmærkninger/LGT	PSN
-		

Bemærkninger: -

2. I "circling" område og på helikopterflyvepladsen

Type ELEV Afmærkninger/LGT	PSN
-	

Bemærkninger: -

7. Heliport Data/Helikopterflyveplads data

AD type	TLOF dimensions	FATO GEO and MAG bearings	FATO dimensions SFC type	TLOF SFC and BRG strength
Circle	20 M diameter	286.0° and 136.0° GEO 308.0° and 158.0° MAG	20 M diameter Gravel	Gravel -
Coordinates of geometric centre TLOF or THR of FATO	TLOF/FATO elevation and slope	Safety area dimensions	HEL CWY dimensions	Obstacle-free zone
60 00 18.53N 044 39 28.40W	42 FT	-	-	-
Remarks/Bemærkninger: -				

8. Declared Distances/Operative banelængder

FATO	TODAH	RTODAH	LDAH
-	-	-	-
Remarks/Bemærkninger: -			

9. Approach and FATO Lighting/Landings- og banebelysning

APP LGT system type, length, intensity	Type of visual approach slope indicator system	FATO area LGT characteristics, location	Aiming point LGT characteristics, location	TLOF LGT system characteristics, location
-	-	-	-	-
Remarks/Bemærkninger: -				

10. ATS Communication Facilities/Lufttrafiktjeneste kommunikationsfaciliteter

Service	CS	FREQ	HR	Remarks
-				

11. Radio Navigation and Landing Aids/Radionavigations- og landingshjælpemidler

FAC VAR	ID	FREQ CH	HR	PSN	DME ELEV	Remarks
-						

12. Additional Information

-

12. Yderligere information

-
