

**STANDARD DEPARTURE CHART -
INSTRUMENT (SID) - ICAO**

**AD 2 - EKCH
RNAV SID RWY 12 - 5
København / Kastrup**

Tabular description:

RNAV RWY 12 via KOPEX 3B

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	SEZAC	Y	119 / (123.2)	-4.0	-	-	-	-	-	RNAV 1
002	DF	CH811	-	-	-4.0	-	R	-	-	-	RNAV 1
003	TF	MAXEL	-	248 / (252.4)	-4.0	29.9	R	-	-	-	RNAV 1
004	TF	KOPEX	-	222 / (226.4)	-4.0	20.8	L	-	-	-	RNAV 1

RNAV RWY 12 via LANGO 3B

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	SEZAC	Y	119 / (123.2)	-4.0	-	-	-	-	-	RNAV 1
002	DF	CH811	-	-	-4.0	-	R	-	-	-	RNAV 1
003	TF	TOBIS	-	256 / (260.1)	-4.0	36.8	R	-	-	-	RNAV 1
004	TF	LANGO	-	233 / (237.2)	-4.0	33.7	L	-	-	-	RNAV 1

RNAV RWY 12 via ODDON 1B

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	SEZAC	Y	119 / (123.2)	-4.0	-	-	-	-	-	RNAV 1
002	DF	CH812	-	-	-4.0	-	L	-	-	-	RNAV 1
003	TF	CH813	-	299 / (302.9)	-4.0	8.3	L	-	-	-	RNAV 1
004	TF	DOBEL	-	243 / (246.6)	-4.0	45.3	L	-	-	-	RNAV 1
005	TF	ODDON	-	263 / (266.9)	-4.0	25.1	R	-	-	-	RNAV 1

RNAV RWY 12 via GOLGA 3B

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	SEZAC	Y	119 / (123.2)	-4.0	-	-	-	-	-	RNAV 1
002	DF	CH812	-	-	-4.0	-	L	-	-	-	RNAV 1
003	TF	CH813	-	299 / (302.9)	-4.0	8.3	L	-	-	-	RNAV 1
004	TF	MIRGO	-	286 / (290.0)	-4.0	22.0	-	-	-	-	RNAV 1
005	TF	GOLGA	-	327 / (330.5)	-4.0	20.6	R	-	-	-	RNAV 1

RNAV RWY 12 via VEDAR 3B

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	SEZAC	Y	119 / (123.2)	-4.0	-	-	-	-	-	RNAV 1
002	DF	CH812	-	-	-4.0	-	L	-	-	-	RNAV 1
003	TF	CH813	-	299 / (302.9)	-4.0	8.3	L	-	-	-	RNAV 1
004	TF	NOVPO	-	309 / (313.3)	-4.0	17.1	-	-	-	-	RNAV 1
005	TF	VEDAR	-	347 / (351.3)	-4.0	25.9	R	-	-	-	RNAV 1

Changes: ODN VOR and ODN 3B withdrawn. WPT ODDON and ODDON 1B added. Editorial.