

**STANDARD DEPARTURE CHART -
INSTRUMENT (SID) - ICAO**

**AD 2 - EKCH
RNAV SID RWY 04 R - 4
København / Kastrup**

Tabular description:

RNAV RWY 04 R via BETUD 2A

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	CH840	Y	037 / (041.4)	-4.0	-	-	-	-	-	RNAV 1
002	TF	CH843	-	036 / (040.1)	-4.0	7.3	-	-	-	-	RNAV 1
003	TF	CH844	-	156 / (160.0)	-4.0	8.8	R	-	-	-	RNAV 1
004	TF	CH845	-	222 / (226.0)	-4.0	7.6	R	-	-	-	RNAV 1
005	TF	BISTA	-	226 / (230.1)	-4.0	29.1	-	-	-	-	RNAV 1
006	TF	BETUD	-	126 / (130.4)	-4.0	18.1	L	-	-	-	RNAV 1

RNAV RWY 04 R via NEXEN 2A

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	CH840	Y	037 / (041.4)	-4.0	-	-	-	-	-	RNAV 1
002	TF	CH843	-	036 / (040.1)	-4.0	7.3	-	-	-	-	RNAV 1
003	TF	CH844	-	156 / (160.0)	-4.0	8.8	R	-	-	-	RNAV 1
004	TF	CH845	-	222 / (226.0)	-4.0	7.6	R	-	-	-	RNAV 1
005	TF	BISTA	-	226 / (230.1)	-4.0	29.1	-	-	-	-	RNAV 1
006	TF	NEXEN	-	212 / (216.3)	-4.0	29.2	-	-	-	-	RNAV 1

RNAV RWY 04 R via KOPEX 2A

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	CH840	Y	037 / (041.4)	-4.0	-	-	-	-	-	RNAV 1
002	TF	CH843	-	036 / (040.1)	-4.0	7.3	-	-	-	-	RNAV 1
003	TF	CH844	-	156 / (160.0)	-4.0	8.8	R	-	-	-	RNAV 1
004	TF	CH845	-	222 / (226.0)	-4.0	7.6	R	-	-	-	RNAV 1
005	TF	CH846	-	255 / (259.1)	-4.0	12.0	R	-	-	-	RNAV 1
006	TF	MAXEL	-	224 / (228.3)	-4.0	24.1	L	-	-	-	RNAV 1
007	TF	KOPEX	-	222 / (226.4)	-4.0	20.8	-	-	-	-	RNAV 1

RNAV RWY 04 R via LANGO 2A

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	CH840	Y	037 / (041.4)	-4.0	-	-	-	-	-	RNAV 1
002	TF	CH843	-	036 / (040.1)	-4.0	7.3	-	-	-	-	RNAV 1
003	TF	CH844	-	156 / (160.0)	-4.0	8.8	R	-	-	-	RNAV 1
004	TF	CH845	-	222 / (226.0)	-4.0	7.6	R	-	-	-	RNAV 1
005	TF	CH848	-	262 / (266.4)	-4.0	18.2	R	-	-	-	RNAV 1
006	TF	TOBIS	-	229 / (233.2)	-4.0	24.2	L	-	-	-	RNAV 1
007	TF	LANGO	-	233 / (237.2)	-4.0	33.7	-	-	-	-	RNAV 1

RNAV RWY 04 R via ODDON 1A

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	CH840	Y	037 / (041.4)	-4.0	-	-	-	-	-	RNAV 1
002	TF	CH841	-	353 / (356.7)	-4.0	10.6	L	-	-	-	RNAV 1
003	TF	CH842	-	288 / (291.7)	-4.0	12.7	L	-	-	-	RNAV 1
004	TF	DOBEL	-	237 / (241.3)	-4.0	36.7	L	-	-	-	RNAV 1
005	TF	ODDON	-	263 / (266.9)	-4.0	25.1	R	-	-	-	RNAV 1

Changes: ODN VOR and ODN 3A withdrawn. WPT ODDON and ODDON 1A added. Editorial.