

**Recommended Coding Tables:**

**BGKK RNP RWY 10**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	ESIBA	-	-	+20.0	-	-	A4300+	-	-	RNP APCH
020	TF	KKI10	-	357 / (336.7)	+20.0	5.0	R	A3500+	-	-	RNP APCH
010	IF	LUNAL	-	-	+20.0	-	-	A5000+	-	-	RNP APCH
020	TF	KKI10	-	087 / (066.5)	+20.0	5.0	-	A3500+	-	-	RNP APCH
010	IF	SOMEV	-	-	+20.0	-	-	A6000+	-	-	RNP APCH
020	TF	KKI10	-	177 / (156.5)	+20.0	7.0	L	A3500+	-	-	RNP APCH
030	TF	KKF10	-	087 / (066.6)	+20.0	4.7	-	A2700+	-	-	RNP APCH
040	TF	KKM10	Y	104 / (083.8)	+20.0	4.7	-	-	-130	3.43°/50	RNP APCH
050	DF	LUNAL	-	-	+20.0	-	L	-	-130	-	RNP APCH
060	HM	LUNAL	Y	087 / (066.5)	+20.0	-	R	A4000	-	-	RNP APCH

**BGKK RNP RWY 10 waypoint coordinates:**

Waypoint Identifier	Coordinates
ESIBA (IAF)	65 27 13.27N 037 30 28.11W
LUNAL (IAF / MAHF)	65 29 48.85N 037 46 14.55W
SOMEV (IAF)	65 38 12.11N 037 41 55.47W
KKI10 (IF)	65 31 47.89N 037 35 13.34W
KKF10 (FAF)	65 33 39.04N 037 24 50.29W
KKM10 (MAPt)	65 34 08.88N 037 13 37.43W

Changes: VAR and MAG bearings changed. Chart designator changed. WP names KKI11, KKF11 and KKM11 changed.