

**STANDARD DEPARTURE CHART -
INSTRUMENT (SID) - ICAO**

**AD 2 - EKCH
RNAV SID RWY 04 L - 5
København / Kastrup**

Tabular description:

RNAV RWY 04 L via ODDON 1E

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	CH839	Y	037 / (041.2)	-4.0	-	-	-	-	-	RNAV 1
002	TF	CH841	-	354 / (358.0)	-4.0	10.4	L	-	-	-	RNAV 1
003	TF	CH842	-	288 / (291.7)	-4.0	12.7	L	-	-	-	RNAV 1
004	TF	DOBEL	-	237 / (241.3)	-4.0	36.7	L	-	-	-	RNAV 1
005	TF	ODDON	-	263 / (266.9)	-4.0	25.1	R	-	-	-	RNAV 1

RNAV RWY 04 L via GOLGA 3E

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	CH839	Y	037 / (041.2)	-4.0	-	-	-	-	-	RNAV 1
002	TF	CH841	-	354 / (358.0)	-4.0	10.4	L	-	-	-	RNAV 1
003	TF	CH842	-	288 / (291.7)	-4.0	12.7	L	-	-	-	RNAV 1
004	TF	MIRGO	-	301 / (305.2)	-4.0	13.9	-	-	-	-	RNAV 1
005	TF	GOLGA	-	327 / (330.5)	-4.0	20.6	R	-	-	-	RNAV 1

RNAV RWY 04 L via VEDAR 3E

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	CH839	Y	037 / (041.2)	-4.0	-	-	-	-	-	RNAV 1
002	TF	CH841	-	354 / (358.0)	-4.0	10.4	L	-	-	-	RNAV 1
003	TF	CH842	-	288 / (291.7)	-4.0	12.7	L	-	-	-	RNAV 1
004	TF	NOVPO	-	341 / (345.4)	-4.0	12.7	R	-	-	-	RNAV 1
005	TF	VEDAR	-	347 / (351.3)	-4.0	25.9	-	-	-	-	RNAV 1

RNAV RWY 04L via KEMAX 2E

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	CH839	Y	037 / (041.2)	-4.0	-	-	-	-	-	RNAV 1
002	TF	CH843	-	039 / (042.7)	-4.0	7.3	-	-	-	-	RNAV 1
003	TF	KEMAX	-	038 / (041.5)	-4.0	31.0	-	-	-	-	RNAV 1

RNAV RWY 04 L via SIMEG 2E

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	CH839	Y	037 / (041.2)	-4.0	-	-	-	-	-	RNAV 1
002	TF	CH843	-	039 / (042.7)	-4.0	7.3	-	-	-	-	RNAV 1
003	TF	CH844	-	156 / (160.0)	-4.0	8.8	R	-	-	-	RNAV 1
004	TF	CH845	-	222 / (226.0)	-4.0	7.6	R	-	-	-	RNAV 1
005	TF	CH847	-	169 / (173.0)	-4.0	11.1	L	-	-	-	RNAV 1
006	TF	SIMEG	-	097 / (101.4)	-4.0	24.2	L	-	-	-	RNAV 1

RNAV RWY 04 L via SALLO 1E

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	CH839	Y	037 / (041.2)	-4.0	-	-	-	-	-	RNAV 1
002	TF	CH843	-	039 / (042.7)	-4.0	7.3	-	-	-	-	RNAV 1
003	TF	CH844	-	156 / (160.0)	-4.0	8.8	R	-	-	-	RNAV 1
004	TF	CH845	-	222 / (226.0)	-4.0	7.6	R	-	-	-	RNAV 1
005	TF	CH847	-	169 / (173.0)	-4.0	11.1	L	-	-	-	RNAV 1
006	TF	SALLO	-	137 / (141.3)	-4.0	31.9	L	-	-	-	RNAV 1

Changes: ODN VOR and ODN 3E withdrawn. VOR ODDON and ODDON 1E added. Editorial.