

Tabular description:

RNAV RWY 22 R via VEDAR 2C

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	RUBAT	Y	217 / (221.2)	-4.0	-	-	-	-	-	RNAV 1
002	DF	CH815	-	-	-4.0	-	R	-	-	-	RNAV 1
003	TF	CH816	-	350 / (354.0)	-4.0	12.0	R	-	-	-	RNAV 1
004	TF	NOVPO	-	353 / (356.8)	-4.0	19.8	-	-	-	-	RNAV 1
005	TF	VEDAR	-	347 / (351.3)	-4.0	25.9	-	-	-	-	RNAV 1

RNAV RWY 22 R via KEMAX 5C

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	RUBAT	Y	217 / (221.2)	-4.0	-	-	-	-	-	RNAV 1
002	DF	CH818	-	-	-4.0	-	L	-	-	-	RNAV 1
003	TF	CH819	-	103 / (106.6)	-4.0	8.1	L	-	-	-	RNAV 1
004	TF	CH821	-	009 / (012.5)	-4.0	16.1	L	-	-	-	RNAV 1
005	TF	KEMAX	-	033 / (037.2)	-4.0	35.9	R	-	-	-	RNAV 1

RNAV RWY 22 R via SIMEG 9C

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	RUBAT	Y	217 / (221.2)	-4.0	-	-	-	-	-	RNAV 1
002	DF	CH818	-	-	-4.0	-	L	-	-	-	RNAV 1
003	TF	CH819	-	103 / (106.6)	-4.0	8.1	L	-	-	-	RNAV 1
004	TF	CH820	-	103 / (106.7)	-4.0	11.3	-	-	-	-	RNAV 1
005	TF	SIMEG	-	103 / (107.0)	-4.0	17.3	-	-	-	-	RNAV 1

RNAV RWY 22 R via SALLO 1C

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	RUBAT	Y	217 / (221.2)	-4.0	-	-	-	-	-	RNAV 1
002	DF	CH818	-	-	-4.0	-	L	-	-	-	RNAV 1
003	TF	CH819	-	103 / (106.6)	-4.0	8.1	L	-	-	-	RNAV 1
004	TF	CH820	-	103 / (106.7)	-4.0	11.3	-	-	-	-	RNAV 1
005	TF	SALLO	-	149 / (153.2)	-4.0	28.2	R	-	-	-	RNAV 1

Changes: Editorial.