

**Instrument Approach Procedure Coding Tables:**

**BGPT RNP RWY 17**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	DOPOK	-	-	+23.0	-	-	+3500	-	-	RNP APCH
020	TF	KUVIG	-	075 / (052.1)	+23.0	5.0	R	+3500	-	-	RNP APCH
010	IF	LOBKA	-	-	+23.0	-	-	+4400	-	-	RNP APCH
020	TF	KUVIG	-	255 / (232.4)	+23.0	5.0	L	+3500	-	-	RNP APCH
030	TF	NOVGO	-	165 / (142.3)	+23.0	5.0	-	+2700	-	-	RNP APCH
040	TF	ROPKI	Y	165 / 142.4)	+23.0	6.0	-	-	-	4.0° / 50	RNP APCH
050	CA	-	-	165 / (142.5)	+23.0	-	-	@1600	-	-	RNP APCH
060	DF	DOPOK	-	-	+23.0	-	R	@3500	-	-	RNP APCH
070	HM	DOPOK	Y	075 / (052.1)	+23.0	-	L	@3500	-	-	RNP APCH

**BGPT RNP RWY 17 waypoint coordinates:**

Waypoint Identifier	Coordinates
DOPOK (IAF)	62 06 41.38 N 050 03 13.33 W
LOBKA (IAF)	62 12 47.20 N 049 46 21.68 W
KUVIG (IAF)	62 09 44.53 N 049 54 48.37 W
NOVGO (FAF)	62 05 47.80 N 049 48 18.11 W
ROPKI (MAPt)	62 01 03.29 N 049 40 32.08 W

Changes: New coding table.