

Instrument Approach Procedure Coding Tables:

EKYT RNP RWY 08L via TOSVO

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	TOSVO	-	-	-4.0	-	-	+2000	-	-	RNP APCH
020	TF	GIPUG	-	169/(172.9)	-4.0	5.0	L	+2000	-	-	RNP APCH
030	TF	YT081	-	079/(083.1)	-4.0	4.6	-	2000	-	-	RNP APCH
040	TF	RW08L	Y	079/(083.1)	-4.0	6.1	-	-	-	3.0°/41	RNP APCH
050	TF	YT083	Y	079/(083.3)	-4.0	5.3	-	-	-	-	RNP APCH
060	HM	YT083	Y	259/(263.3)	-4.0	-	R	+2000	-	-	RNP APCH

EKYT RNP RWY 08L via KUDEV

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	KUDEV	-	-	-4.0	-	-	+2300	-	-	RNP APCH
020	TF	GIPUG	-	349/(352.9)	-4.0	5.0	R	+2000	-	-	RNP APCH
030	TF	YT081	-	079/(083.1)	-4.0	4.6	-	2000	-	-	RNP APCH
040	TF	RW08L	Y	079/(083.1)	-4.0	6.1	-	-	-	3.0°/41	RNP APCH
050	TF	YT083	Y	079/(083.3)	-4.0	5.3	-	-	-	-	RNP APCH
060	HM	YT083	Y	259/(263.3)	-4.0	-	R	+2000	-	-	RNP APCH

EKYT RNP RWY 08L waypoint coordinates:

Waypoint Identifier	Coordinates
TOSVO (IAF)	57 09 16.80N 009 29 19.21E
KUDEV (IAF)	56 59 23.12N 009 31 34.48E
GIPUG (IF)	57 04 20.00N 009 30 27.00E
YT081 (FAF)	57 04 53.88N 009 38 54.12E
RW08L (MAPt)	57 05 37.37N 009 50 00.30E
YT083 (MAHF)	57 06 13.39N 009 59 44.08E

Changes: VAR and MAG bearings.