

Instrument Approach Procedure Coding Tables:

BGUK RNP A via UPDAS, ELMUT and ROVIN

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	UPDAS	-	-	+33.0	-	-	A5100+	-	-	RNP APCH
020	TF	UKI04	-	149 / (116.0)	+33.0	5.0	L	A3300+	-	-	RNP APCH
010	IF	ELMUT	-	-	+33.0	-	-	A3400+	-	-	RNP APCH
020	TF	UKI04	-	059 / (026.1)	+33.0	5.0	-	A3300+	-	-	RNP APCH
010	IF	ROVIN	-	-	+33.0	-	-	A5100+	-	-	RNP APCH
020	TF	UKI04	-	329 / (296.4)	+33.0	5.0	R	A3300+	-	-	RNP APCH
030	TF	UKF04	-	059 / (026.2)	+33.0	5.0	-	A2700+	-	-	RNP APCH
040	TF	UKM04	Y	059 / (026.3)	+33.0	5.3	-	-	-	3.50°/ 50	RNP APCH
050	CA	-	-	059 / (026.3)	+33.0	-	-	A1500+	-	-	RNP APCH
060	DF	UPDAS	-	-	+33.0	-	L	A3300	-	-	RNP APCH
070	HM	UPDAS	Y	149 / (116.0)	+33.0	-	R	A3300	-	-	RNP APCH

BGUK RNP A waypoint coordinates:

Waypoint Identifier	Coordinates
UPDAS (IAF)	72 39 28.41N 056 38 41.81W
ELMUT (IAF)	72 32 48.97N 056 31 03.81W
ROVIN (IAF)	72 35 04.71N 056 08 49.32W
UKI04 (IF)	72 37 17.15N 056 23 44.36W
UKF04 (FAF)	72 41 45.04N 056 16 21.26W
UKM04 (MAPt)	72 46 27.76N 056 08 29.01W

Changes : VAR and MAG bearings updated. Chart designator changed. Altitude at UPDAS and ROVIN changed. WP identifiers changed due change of RWY designator.