

Instrument Approach Procedure Coding Tables:

LOC Z RWY 09 initial approach via BELZI, DODIP and KEFOP.:

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	BELZI	-	-	+27.0	-	-	+5400	-	-	RNP 1
020	TF	KEFOP	-	178 / (151.0)	+27.0	6.0	L	+4000	-	-	RNP 1
010	IF	DODIP	-	-	+27.0	-	-	+5200	-	-	RNP 1
020	TF	KEFOP	-	358 / (331.2)	+27.0	6.0	R	+4000	-	-	RNP 1
020	IF	KEFOP	-	-	+27.0	-	-	+4000	-	-	RNP 1
030	TF	SF09F	-	088 / (061.1)	+27.0	6.9	-	+2500	-	-	RNP 1

BGSF LOC Z RWY 09 missed approach procedure:

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	CA	-	-	088 (061.6)	+27.0	-	L	+2900	-	-	RNP 1
020	DF	KEFOP	-	-	+27.0	-	-	@4000	-	-	RNP 1
030	HM	KEFOP	Y	088 (061.1)	+27.0	-	R	@4000	-	-	RNP 1

BGSF LOC Z RWY 09 waypoint coordinates:

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
BELZI (IAF)	66 59 04.35N 051 22 18.22W	DODIP (IAF)	66 48 35.97N 051 07 35.45W
KEFOP (IAF/IF)	66 53 50.33N 051 14 55.26W	SF09F (FAF)	66 57 09.68N 050 59 29.97W

Changes: Altitude changed at DODIP.