

Instrument Approach Procedure Coding Tables:

BGAA RNP RWY 29 via USEPO, DEVKA and EKTUD

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	USEPO	-	-	+29.0	-	-	A2500+	-	-	RNP APCH
020	TF	DEVKA	-	218 / (188.7)	+29.0	5.0	R	A2500+	-	-	RNP APCH
010	IF	DEVKA	-	-	+29.0	-	-	A2800+	-	-	RNP APCH
010	IF	EKTUD	-	-	+29.0	-	-	A2500+	-	-	RNP APCH
020	TF	DEVKA	-	358 / (328.8)	+29.0	5.0	L	A2500+	-	-	RNP APCH
030	TF	AAF29	-	288 / (258.7)	+29.0	4.0	-	A2000+	-	-	RNP APCH
040	TF	RW29	Y	288 / (258.5)	+29.0	5.5	-	-	-	3.20°/50	RNP APCH
050	CA	-	-	288 / (258.5)	+29.0	-	-	A1000+	-	-	RNP APCH
060	DF	DEVKA	-	-	+29.0	-	R	-	-	-	RNP APCH
070	HM	DEVKA	Y	288 / (258.7)	+29.0	-	R	A2500	-	-	RNP APCH

BGAA RNP RWY 29 waypoint coordinates:

Waypoint Identifier	Coordinates
USEPO (IAF)	68 50 10.98N 052 18 44.89W
EKTUD (IAF)	68 40 59.93N 052 13 42.15W
DEVKA (IAF/IF/MAHF)	68 45 15.44N 052 20 49.49W
AAF29 (FAP/FAF)	68 44 28.08N 052 31 35.67W
RW29 (MAPt)	68 43 21.28N 052 46 30.33W

Changes: New procedure.