1. Location Indicator/Name: BGAP - Alluitsup Paa

2. Geographical and Administrative Data

1.	ARP PSN and site:	60 27 52.05N 045 34 08.77W
2.	Distance and direction from city:	Located in northern part of Alluitsup Paa town
3.	ELEV: REF temperature:	89 FT -
4.	MAG VAR: Annual change:	23° W (JUN 2015) Decreasing 18'
5.	ADM:	Greenland Airports A/S
	Address:	KNI A/S Alluitsup Paa B110 DK-3919 Alluitsup Paa Greenland TEL: +299 86 81 69 +299 86 81 67 FAX: - E-mail: 028alluitsuppaa@kni.gl AFS: -
6.	Types of traffic permitted:	VMC daylight
7.	Remarks:	1. Start or landing must only take place when average wind velocity is 25 KT or below, due to reduced safety zone around FATO. 2. Maximum D-value limited to 18 M. 3. MTOM limited to 10 tonnes. 4. Maximum number of passenger seats limited to 19.

3. Operational Hours

1.	AD:	MON-FRI 1100-1800 (1000-1700) SAT/SUN/HOL CLSD Open for scheduled flights. For non-scheduled flights PPR 48 HR.
2.	Fuelling:	-

4. Aprons, Taxiways and Check Locations Data

1.	Helicopter stand surface and strength:	Asphalt -

5. Markings

1.	Final approach and take-off markings:	Red/white truncated cones
2.	TWY, air TWY, air transit route markers:	-
3.	Remarks:	-

6. Heliport Obstacles

1. In APCH and TKOF areas

RWY Area affected	Type ELEV Markings/LGT	PSN
-		

Remarks: -

2. In circling area and at Heliport

Type ELEV Markings/LGT	PSN
-	

Remarks: -

1. Stedindikator/navn: BGAP - Alluitsup Paa

2. Geografiske og administrative data

1.	ARP PSN og beliggenhed:	60 27 52.05N 045 34 08.77W
2.	Afstand og retning fra by:	Beliggende i den nordlige del af Alluitsup Paa by
3.	ELEV: REF temperatur:	89 FT -
4.	MAG VAR: Årlig ændring:	23° W (JUN 2015) Aftagende 18'
5.	ADM:	Greenland Airports A/S
	Adresse:	KNI A/S Alluitsup Paa B110 DK-3919 Alluitsup Paa Grønland TEL: + 86 81 69 + 86 81 67 FAX: - E-mail: 028alluitsuppaa@kni.gl AFS: -
6.	Tilladte trafiktyper:	VMC dag
7.	Bemærkninger:	1. Start eller landing må kun finde sted når middelvindhastigheden er 25 KT eller derunder, på grund af reduceret sikkerhedszone omkring FATO. 2. Maks D-værdi begrænses til 18 M. 3. MTOM begrænses til 10 tons. 4. Maks antal passagersæder begrænses til 19.

3. Tjenestetid

1.	AD:	MON-FRI 1100-1800 (1000-1700) SAT/SUN/HOL CLSD Åben for rutetrafik. For ikke-regelmæssig trafik PPR 48 HR.
2.	Tankning:	-

4. Forpladser, rulleveje og checkpunkt data

1.	Helikopterstandplads overflade og styrke:	Asfalt -

5. Afmærkning

1.	Landings- og start-afmærkning:	Rød/hvide keglestubbe
2.	TWY, luft TWY, luft transit rute afmærkninger:	-
3.	Bemærkninger:	-

6. Helikopterflyveplads hindringer

1. I APCH og TKOF områder

RWY Berørt område	Type ELEV Afmærkninger/LGT	PSN
-		

Bemærkninger: -

2. I "circling" område og på helikopterflyvepladsen

Type ELEV Afmærkninger/LGT	PSN
-	

Bemærkninger: -

7. Heliport Data/Helikopterflyveplads data

AD type	TLOF dimensions	FATO GEO and MAG bearings	FATO dimensions SFC type	TLOF SFC and BRG strength
Circle	18 M diameter	043.8° and 223.8° GEO 066.8° and 246.8° MAG	18 M diameter Artificial Turf/Kunstgræs	Asphalt 073.0°/253.0° GEO

Coordinates of geometric centre TLOF or THR FATO	TLOF/FATO elevation and slope	Safety area dimensions	HEL CWY dimensions	Obstacle-free zone
60 27 52.05N 045 34 08.77W	89 FT	-	-	-

Remarks/Bemærkninger: -

8. Declared Distances/Operative banelængder

FATO	TODAH	RTODAH	LDAH
-	-	-	-

Remarks/Bemærkninger: -

9. Approach and FATO Lighting/Landings- og banebelysning

APP LGT system type, length, intensity	Type of visual approach slope indicator system	FATO area LGT characteristics, location	Aiming point LGT characteristics, location	TLOF LGT system characteristics, location
-	-	-	-	-

Remarks/Bemærkninger: -

10. ATS Communication Facilities/Lufttrafiktjeneste kommunikationsfaciliteter

Service	CS	FREQ	HR	Remarks
-				

11. Radio Navigation and Landing Aids/Radionavigations- og landingshjælpemidler

FAC VAR	ID	FREQ CH	HR	PSN	DME ELEV	Remarks
-						

12. Additional Information

-

12. Yderligere information

-