

**Tabular description**

**RNAV RWY 12 via TESPI**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
001	IF	TESPI	-	-	-4.0	-	-	-	-	-	RNAV 1
002	TF	ROSB1	-	098 / (102.1)	-4.0	13.9	-	-	-	-	RNAV 1
003	TF	TNO	-	101 / (104.6)	-4.0	17.8	-	-FL130	-250	-	RNAV 1
004	TF	CH553	-	118 / (121.6)	-4.0	10.0	R	-	-	-	RNAV 1
005	TF	CH542	-	118 / (121.8)	-4.0	10.0	-	-	-	-	RNAV 1
006	TF	CH533	-	118 / (122.0)	-4.0	9.1	-	-	-	-	RNAV 1
007	TF	CH525	-	029 / (032.5)	-4.0	8.5	L	-	-	-	RNAV 1
008	TF	AGTIC	-	299 / (302.6)	-4.0	5.0	L	-4000	@220	-	RNAV 1
009	FM	AGTIC	-	299 / (302.6)	-4.0	-	-	-	-	-	RNAV 1

**RNAV RWY 12 via TUDLO**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
001	IF	TUDLO	-	-	-4.0	-	-	-	-	-	RNAV 1
002	TF	LUGAS	-	069 / (073.2)	-4.0	11.3	-	-	-	-	RNAV 1
003	TF	KOR	-	070 / (073.7)	-4.0	23.8	-	-FL120	-250	-	RNAV 1
004	TF	CH543	-	071 / (075.3)	-4.0	10.1	-	-	-	-	RNAV 1
005	TF	CH533	-	072 / (075.5)	-4.0	8.7	-	-	-	-	RNAV 1
006	TF	CH525	-	029 / (032.5)	-4.0	8.5	L	-	-	-	RNAV 1
007	TF	AGTIC	-	299 / (302.6)	-4.0	5.0	L	-4000	@220	-	RNAV 1
008	FM	AGTIC	-	299 / (302.6)	-4.0	-	-	-	-	-	RNAV 1

**RNAV RWY 12 via MONAK**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
001	IF	MONAK	-	-	-4.0	-	-	-	-	-	RNAV 1
002	TF	OLPIB	-	030 / (034.0)	-4.0	4.1	-	-	-	-	RNAV 1
003	TF	NEKSO	-	030 / (033.8)	-4.0	16.7	-	-	-250	-	RNAV 1
004	TF	CH546	-	022 / (025.8)	-4.0	14.2	-	-FL090	-	-	RNAV 1
005	TF	CH530	-	299 / (303.0)	-4.0	16.5	L	-	-	-	RNAV 1
006	TF	CH525	-	299 / (302.7)	-4.0	5.0	-	-	-	-	RNAV 1
007	TF	AGTIC	-	299 / (302.6)	-4.0	5.0	-	-4000	@220	-	RNAV 1
008	FM	AGTIC	-	299 / (302.6)	-4.0	-	-	-	-	-	RNAV 1

**RNAV RWY 12 via TIDVU**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
001	IF	TIDVU	-	-	-4.0	-	-	-	-	-	RNAV 1
002	TF	WUPJA	-	319 / (322.6)	-4.0	16.3	-	-	-250	-	RNAV 1
003	TF	CH545	-	278 / (282.4)	-4.0	7.6	L	-FL080	-	-	RNAV 1
004	TF	CH535	-	279 / (282.8)	-4.0	10.2	-	-	-	-	RNAV 1
005	TF	CH524	-	299 / (303.0)	-4.0	11.3	R	-	-	-	RNAV 1
006	TF	FEDJO	-	299 / (302.7)	-4.0	5.0	-	-4000	@220	-	RNAV 1
007	FM	FEDJO	-	299 / (302.7)	-4.0	-	-	-	-	-	RNAV 1

**RNAV RWY 12 via ERNOV**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
001	IF	ERNOV	-	-	-4.0	-	-	-FL110	-250	-	RNAV 1
002	TF	CH532	-	171 / (175.1)	-4.0	15.5	-	-	-	-	RNAV 1
003	TF	CH524	-	209 / (212.8)	-4.0	8.5	R	-	-	-	RNAV 1
004	TF	FEDJO	-	299 / (302.7)	-4.0	5.0	R	-4000	@220	-	RNAV 1
005	FM	FEDJO	-	299 / (302.7)	-4.0	-	-	-	-	-	RNAV 1

Changes: WPT CDA withdrawn and WPT OLPIB added. Editorial.