

**Instrument Approach Procedure Coding Tables:**

**BGSS RNP B via ULGED and MOPZU**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	ULGED	-	-	+28.0	-	-	A8000+	-	-	RNP APCH
020	TF	SS401	-	287 / (258.5)	+28.0	11.7	-	A6000+	-	-	RNP APCH
030	TF	SSI41	-	286 / (258.0)	+28.0	12.0	R	A3000+	-	-	RNP APCH
010	IF	MOPZU	-	-	+28.0	-	-	A9500+	-	-	RNP APCH
020	TF	SS402	-	030 / (002.2)	+28.0	10.9	-	A6000+	-	-	RNP APCH
030	TF	SSI41	-	030 / (002.2)	+28.0	10.0	L	A3000+	-	-	RNP APCH
040	TF	SSF41	-	331 / (302.7)	+28.0	4.0	-	A2200+	-	-	RNP APCH
050	TF	SSM41	Y	331 / (302.5)	+28.0	5.0	-	-	-	3.50' / -	RNP APCH
060	CA	-	-	331 / (302.5)	+28.0	-	-	A2000+	-	-	RNP APCH
070	DF	SEFUN	-	-	+28.0	-	L	-	-	-	RNP APCH
080	HM	SEFUN	Y	041 / (013.3)	+28.0	-	L	A2800	-	-	RNP APCH

**BGSS RNP B waypoint coordinates:**

Waypoint Identifier	Coordinates
ULGED (IAF)	66 56 24.21N 052 27 30.07W
MOPZU (IAF)	66 30 41.30N 053 28 22.87W
SS401	66 54 01.43N 052 56 38.63W
SS402	66 41 32.14N 053 27 20.77W
SSI41 (IF)	66 51 29.71N 053 26 23.02W
SSF41 (FAF)	66 53 38.55N 053 34 55.67W
SSM41 (MAPt)	66 56 18.94N 053 45 38.58W
SEFUN (MAHF)	66 55 28.00N 054 20 37.00W

Changes: New procedure.