

**Instrument Approach Procedure Coding Tables:
EKEB RNP RWY 26 via TITBA, HUCXA and UTURO**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed (kt)	VPA/TCH	Navigation Specification
010	IF	TITBA	-	-	-3.0	-	-	+2000	-	-	RNP APCH
020	TF	EB262	-	167 / (169.7)	-3.0	5.0	R	+2000	-240	-	RNP APCH
010	IF	HUCXA	-	-	-3.0	-	-	+2000	-	-	RNP APCH
020	TF	EB262	-	262 / (264.3)	-3.0	7.4	L	+2000	-	-	RNP APCH
010	IF	UTURO	-	-	-3.0	-	-	+2000	-	-	RNP APCH
020	TF	EB262	-	327 / (329.8)	-3.0	5.0	L	+2000	-	-	RNP APCH
010	IF	EB262	-	-	-3.0	-	-	+2000	-	-	RNP APCH
020	TF	EB261	-	257 / (259.8)	-3.0	4.1	-	+2000	-	-	RNP APCH
030	TF	RW26	Y	257 / (259.7)	-3.0	5.8	-	-	-	3.00 / 50	RNP APCH
040	TF	EB263	-	257 / (259.5)	-3.0	3.4	L	-	-	-	RNP APCH
050	TF	TOMMO	-	252 / (254.5)	-3.0	12.9	-	+2000/-FL080	-	-	RNP APCH
060	HM	TOMMO	Y	054 / (057.1)	-3.0	-	R	+2000/-FL080	-210	-	RNP APCH

EKEB RNP RWY 26 waypoint coordinates:

Waypoint Identifier	Coordinates	Waypoint Identifier	Coordinates
TITBA (IAF)	55 38 22.85N 008 50 02.72E	EB261 (FAF/FAP)	55 32 44.20N 008 44 30.83E
HUCXA (IAF)	55 34 12.73N 009 04 35.27E	EB262 (IF)	55 33 28.09N 008 51 36.96E
UTURO (IAF)	55 29 09.26N 008 56 02.72E	EB263 (MATF)	55 31 04.20N 008 28 35.62E
TOMMO (MAHF)	55 27 35.86N 008 06 41.87E	RW26 (MAPt)	55 31 41.16N 008 34 26.23E

Changes: WPT HAJAQ changed to HUCXA.