

**Tabular description:**

**RNAV RWY 04 R via GOLGA 3A**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	CH840	Y	037 / (041.4)	-4.0	-	-	-	-	-	RNAV 1
002	TF	CH841	-	353 / (356.7)	-4.0	10.6	L	-	-	-	RNAV 1
003	TF	CH842	-	288 / (291.7)	-4.0	12.7	L	-	-	-	RNAV 1
004	TF	MIRGO	-	301 / (305.2)	-4.0	13.9	-	-	-	-	RNAV 1
005	TF	GOLGA	-	327 / (330.5)	-4.0	20.6	R	-	-	-	RNAV 1

**RNAV RWY 04 R via VEDAR 4A**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	CH840	Y	037 / (041.4)	-4.0	-	-	-	-	-	RNAV 1
002	TF	CH841	-	353 / (356.7)	-4.0	10.6	L	-	-	-	RNAV 1
003	TF	CH842	-	288 / (291.7)	-4.0	12.7	L	-	-	-	RNAV 1
004	TF	NOVPO	-	341 / (345.4)	-4.0	12.7	R	-	-	-	RNAV 1
005	TF	VEDAR	-	347 / (351.3)	-4.0	25.9	-	-	-	-	RNAV 1

**RNAV RWY 04 R via KEMAX 5A**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	CH840	Y	037 / (041.4)	-4.0	-	-	-	-	-	RNAV 1
002	TF	CH843	-	036 / (040.1)	-4.0	7.3	-	-	-	-	RNAV 1
003	TF	KEMAX	-	038/ (041.5)	-4.0	31.0	-	-	-	-	RNAV 1

**RNAV RWY 04 R via SIMEG 8A**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	CH840	Y	037 / (041.4)	-4.0	-	-	-	-	-	RNAV 1
002	TF	CH843	-	036 / (040.1)	-4.0	7.3	-	-	-	-	RNAV 1
003	TF	CH844	-	156 / (160.0)	-4.0	8.8	R	-	-	-	RNAV 1
004	TF	CH845	-	222 / (226.0)	-4.0	7.6	R	-	-	-	RNAV 1
005	TF	CH847	-	169 / (173.0)	-4.0	11.1	L	-	-	-	RNAV 1
006	TF	SIMEG	-	097 / (101.4)	-4.0	24.2	L	-	-	-	RNAV 1

**RNAV RWY 04 R via SALLO 1A**

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft) Upper / Lower	Speed (kt)	VPA/TCH	Navigation Specification
001	CF	CH840	Y	037 / (041.4)	-4.0	-	-	-	-	-	RNAV 1
002	TF	CH843	-	036 / (040.1)	-4.0	7.3	-	-	-	-	RNAV 1
003	TF	CH844	-	156 / (160.0)	-4.0	8.8	R	-	-	-	RNAV 1
004	TF	CH845	-	222 / (226.0)	-4.0	7.6	R	-	-	-	RNAV 1
005	TF	CH847	-	169 / (173.0)	-4.0	11.1	L	-	-	-	RNAV 1
006	TF	SALLO	-	137 / (141.3)	-4.0	31.9	L	-	-	-	RNAV 1

Changes: Editorial.